

# Building Blocks of Python Programs

# Comments

We want people to be able to read and understand our programs. The **#** symbol introduces a *comment*, which is a note for human readers of the code. Comments are ignored by computers. Anything to the right of a **#** symbol is part of the comment and ignored.

You should get in the habit of putting a comment at the top of every program saying at least

a) Your name

b) What the program does

Here is a nice format for this

```
# gradebook.py
```

```
# This simulates a digital gradebook
```

```
# author: Bob Geitz
```

```
# Last modified January 29, 2015
```

# Variables

A variable is a name that represents something in your program.

Variables start with a letter and consist of letters, digits, and underscores. No spaces, periods, hyphens, etc.

Here are some good variable names

averageScore

letterCount

letter\_count

Most programming languages require variables to be *declared*, which requires saying what kind of data the variable can hold. There are no variable declarations in Python. You create a variable by giving it a value, as in

```
x = 5
```

**Assignment statements** give values to variables.

We use = for this. We can say

`x = 5`

`x = 6`

The first use of a variable creates it, so the line `x=5` creates variable `x` and puts the value 5 into it. The line `x=6` changes the value stored in `x` to 6.

Don't confuse = (for assignments) with == (for comparisons)

Here are 4 simple **types of data**:

- **Integers:** 2, -3, 0
- **Floats:** 3.14, -6.2, 5.0
- **Strings:** "Bob", "Oberlin College", ""
- **Booleans:** True, False

# Integer data

- Read with `eval(input( <prompt> ))`

as in

```
x = eval( input( "Enter a number: " ) )
```

- Arithmetic operations `+`, `*`, `-`, `/`, `//`, `%`, `**`
- `/` is for floating point division: `7/2` is `3.5`
- `//` is for integer division: `7/2` is `3`
- `**` is for exponentiation: `3**4` is `81`
- `%` is the modulus (or remainder) operation  
`7 % 5` is `2`

Note that % (the modulus or remainder operator) is more useful than you might think:

- I usually pronounced  $a\%b$  as "a mod b"  
Some people say "a remainder b"
- b divides evenly into a if  $a\%b$  is 0
- x is even if  $x\%2$  is 0; x is odd if  $x\%2$  is 1
- days d1 and d2 of a given month fall on the same day of the week if  $d1\%7$  is the same as  $d2\%7$ .

The Arithmetic Rule for operators +, -, \*

If a and b are both integers, then  $a \text{ op } b$  is an int.

If either a or b or both are floats, then  $a \text{ op } b$  is a float.

There isn't a lot to say about floats except that they are there. Internally the integer 3 is stored in a completely different way than the float 3.0. This makes comparing floats and integers for equality problematic.

You can convert an int `x` to a float with

```
float(x)
```

as in

```
float(3)
```

which gives you 3.0.

# Strings

- Strings are delimited with either single quotes: 'bob'  
or double quotes: "bob"
- read with `input( )`
- if `blah` is a string that represents a valid Python expression, then `eval(blah)` gets the value of that expression:
  - `eval("4")` is 4.

- The + operator between 2 strings *concatenates* or pushes the strings together.  
"Marvin " + "Krislov" is "Marvin Krislov"
- The comparison operators <, <=, ==, >=, >, != compare strings in dictionary order, only all of the capital letters come before all of the lower-case ones.

You can use indexes to get at the individual characters (letters) of a string. We always start indexing at 0.

Suppose  $s$  is the string "abcd". Then  $s[0]$  is "a",  $s[1]$  is "b", and so forth. The number of characters in string  $s$  is  $\text{len}(s)$ . So the valid indexes of string  $s$  are any integers between 0 and  $\text{len}(s)-1$ .

`s[a, b]` is the portion of string `s` starting at index `a`, going up to but not including index `b`. So if `s` is "Bob the Great", `s[4:7]` is "the". Similarly `s[a:]` is all of `s` starting with index `a`, and `s[:b]` is the portion of `s` up to but not including index `b`.

You can even use negative indexes: `s[-1]` is the last character of string `s`. But I find it easy to get confused with negative indexes so I tend to avoid them.

Finally, if `s` is a string then `s.upper()` is `s` with its lower-case letters converted to upper-case.  
`"23 skidoo".upper()` is `"23 SKIDOO"`.

There is a similar `.lower()` method that converts upper-case letters to lower-case.

**Booleans** (named after George Boole, a British logician)

There are two Boolean values: **True** and **False**.  
Note the capitalization: true has no meaning in Python, True does.

You can connect two Boolean expression with **and**, **or**, **not**.

Here is an expression that says variable x has a value between 1 and 10:

```
if (x >= 1) and (x <= 10):  
    blah blah blah
```

It is possible in Python to write this as

```
1 <= x <= 10
```

but I have seen so many people do that incorrectly that I much prefer to write compound expressions with explicit operators like **and**, **or**.